

STINGRAY 12090 CLAMSHELL

SPECIFICATIONS

Standard Features & General Construction:

- Green** Technology: Closed Loop Zero Discharge
- ClamShell Door Design for Maximum Turntable Access
- Electronic Water Level Control & Refill
- Oscillating Wash Manifold to Maximize Cleaning
- Easy to Service Wash Pump Suction Strainer
- Adjustable Electronic Temp Control, Temp Gage
- Control Transformer External of Panel minimizes Heat
- Programmable 24 Hour 7 Day Clock
- Low Water Shut-Off Protects Pumps & Heating System
- Electronic Door Safety Interlock
- Wash Cycle Timer with Auto Reset
- Heavy gage 1/4" Sheet Steel Cabinet Thickness
- 230 V or 460 V- 60 Hz 3-Phase with 120 V Controls
- Chemical Resistant Two Part 3 mil Epoxy Coating



Spray Manifold:

OSCILLATING NON- SYNCHRONOUS

Angle of Oscillation:	40 degrees
Frequency of Oscillation:	4 per minute
Number of Wash Nozzles:	32
Type of Nozzle:	Vee-Jet
Nozzle Material:	316 Stainless
Nozzle Spray Pattern:	25 degrees

Overall Dimensions:

Width: (Std Unit)	164 inches
Depth: (Std Unit)	158 inches
Height:	160 inches
Empty Weight:	25,500 lbs
Reservoir Capacity:	994 gallons
Quadroplex	Add 77 gallons
Sludge Capacity:	180 gallons

Work Area Dimensions:

Turntable Diameter:	120 inches
Work Height:	90 inches
Table Load Capacity:	28,000 lbs
Heavy Duty Capacity:	60,000 lbs

Heat System:

Operating Temperature:	180 degrees F
Initial Heat-Up Time:	120 MINUTES
Electric Heat Element Size:	120 kW
Gas/Propane Eclipse 80% Eff	990,000 BTU/hr
Equivalent Electric Heat	230 kW

Electrical:

Wiring Standard:	NFPA 79	Motor Rating:	Continuous Duty
Motor Starters:	Across the line	Motor Enclosures:	TEFC
Short Circuit Protection:	Std	Electrical Enclosures:	NEMA 12
Overload Protection:	Std	Wiring Conduit:	Flex- Non-Metallic
Motor Type:	Energy-Efficient	Conduit Type:	Liquidtight NEMA12

Pump System & Performance:

High Efficiency, Rated for continuous duty (20 Start/hour without overheating), vertical, centrifugal, seal-less, balanced, enclosed impeller.

Note: All performance data taken at nozzle discharge.

STANDARD:

Pump System	70 hp
Total System Flow:	502 gpm
Flow per Nozzle:	15.7 gpm
System Pressure:	152 psi
Blast Velocity:	156 ft/sec

OPTIONAL:

140 hp	140 hp
1004 gpm	860 gpm
15.7 gpm	19.9 gpm
152 psi	190 psi
156 ft/sec	198 ft/sec

Results may vary based on machine configuration.





E-mail: sales@StingWash.com

[Website: www.StingRayPartsWasher.com](http://www.StingRayPartsWasher.com)

12090
