

STINGRAY 5248

SPECIFICATIONS



Standard Features & General Construction:

- Green Technology:** Closed Loop Zero Discharge
- Swing Door Retracting Turntable for Maximum Access
- Electronic Water Level Control & Refill
- Oscillating Wash Manifold to Maximize Cleaning
- Easy to Service Front Wash Pump Suction Strainer
- Adjustable Electronic Temp Control, Temp Gage
- Control Transformer External of Panel minimizes Heat
- Programmable 24 Hour 7 Day Clock
- Low Water Shut-Off Protects Pumps & Heating System
- Electronic Door Safety Interlock
- Wash Cycle Timer with Auto Reset
- Heavy gage 3/16" Sheet Steel Cabinet Thickness
- 230 V or 460 V- 60 Hz 3-Phase with 120 V Controls
- Chemical Resistant Two Part, 3 mm Epoxy Coating in Blue

Spray Manifold:

OSCILLATING NON- SYNCHRONOUS

Angle of Oscillation:	39 degrees
Frequency of Oscillation:	4 per minute
Number of Wash Nozzles:	20
Type of Nozzle:	Vee-Jet
Nozzle Material:	316 Stainless
Nozzle Spray Pattern:	25 degrees

Overall Dimensions:

Width: (Std Unit)	98 inches
Depth: (Std Unit)	87 inches
Height:	93 inches
Empty Weight:	5,800 lbs
Reservoir Capacity:	265 gallons
Duplex Reservoir:	Add 47 gallons
Sludge Capacity:	75 gallons

Work Area Dimensions:

Turntable Diameter:	52 inches
Cleaning Work Height:	48 inches
Turntable Height above Floor:	34.5 inches
Table Load Capacity:	2,500 lbs
Heavy Duty Capacity:	7,000 lbs

Heat System:

Operating Temperature:	140 - 190 degrees F
Initial Heat-Up Time:	60 - 90 minutes
Element Size:	60 kW
Gas/Propane Eclipse 80% Eff	400,000 BTU/hr

Electrical:

Wiring Standard:	NFPA 79	Motor Rating:	Continuous Duty
Motor Starters:	Across the line	Motor Enclosures:	TEFC
Short Circuit Protection:	Std	Electrical Enclosures:	NEMA 12
Overload Protection:	Std	Wiring Conduit:	Flex- Non-Metallic
Motor Type:	Industrial	Type of Conduit:	Liquidtight IP65

Pump System & Performance:

High Efficiency, Rated for continuous duty (20 Start/hour without overheating), vertical, centrifugal, seal-less, balanced, enclosed impeller.

Note: All performance data taken at nozzle discharge.

STANDARD:

20 hp

Total System Flow:	269 gpm
Flow per Nozzle:	13.5 gpm
System Pressure:	107 psi
Blast Velocity:	126 ft/sec

UPGRADES: (Simplex)

30 hp 40 hp

301 gpm	319 gpm
15.1 gpm	16.0 gpm
134 psi	150 psi
141 ft/sec	149 ft/sec

UPGRADES: (Duplex)

55 hp 70 hp

356 gpm	371 gpm
17.8 gpm	18.6 gpm
187 psi	203 psi
166 ft/sec	173 ft/sec

Results and Dimensions may vary based on machine configuration.



STINGRAY MANUFACTURING
 2450 Adie Road • St. Louis, MO 63043 USA
 Phone: (314)447-9000 • Fax: (314)447-0909
 Email: sales@stingwash.com • www.stingwash.com