

STINGRAY 5248 SPECIFICATIONS

Standard Features & General Construction:

Oscillating Manifold: Non-Synchronous to the Turntable - Maximizes Cleaning.
Swing Door Retracting, Door-Mounted Turntable: Allows for Maximum Access.
Closed-Loop, Zero Discharge Cleaning Process: Environmentally Friendly.
Heated Fresh Water Rinse: Removes Residual Detergent (Optional).
Automatic Steam Exhaust: Facilitates Flash Drying of Parts.
Non-Intersecting Stainless Steel V-Jet Nozzles: Blasts Parts Clean.
Heavy 7-Gauge, 3/16" Sheet Steel Cabinet.
Electronic Water Level Control: Maintains Proper Solution Level.
Programmable 24-Hour 7-Day Clock: Delivers Simple Operation.
Wash Cycle Timer with Auto Reset: Effortless Cleaning Cycle Programming.
Easy Access Solution Tank: Delivers Trouble-Free Maintenance.
Electronic Door Safety Interlock: Prevents Operation if Switch Fails.
StingRay Blue, 2-Part, 3 mil Epoxy Coating: Withstands Cleaning Chemicals.
Adjustable Electronic Temp Control, Temp Gauge, Digital 2-Line Display
Control Transformer External of Panel: Minimizes Heat.
Low Water Shut-Off: Protects Pumps & Heating System.
Quality Conforms to ISO9001 and OSHA-Compliant



Power Blast Manifold:

OSCILLATING NON- SYNCHRONOUS

Angle of Oscillation:	39 degrees
Frequency of Oscillation:	4 per minute
Number of Wash Nozzles:	20
Type of Nozzle:	Vee-Jet
Nozzle Material:	316 Stainless
Nozzle Spray Pattern:	25 degrees

Heat System:


Operating Temperature:	140 - 190 degrees F
Initial Heat-Up Time:	60 - 90 minutes
Element Size:	60 kW
Gas/Propane Eclipse 80% Eff	400,000 BTU/hr
Gas/Propane Riello	200,000 BTU/hr

Base Machine Work Area Dimensions:

Turntable Diameter:	52 inches
Cleaning Work Height:	48 inches
Turntable Height above Floor:	34.5 inches
Table Load Capacity:	2,500 lbs
Heavy Duty Capacity:	7,000 lbs

Base Machine Overall Dimensions:

Width: (Std Unit)	98 inches
Depth: (Std Unit)	87 inches
Height:	93 inches
Empty Weight:	5,800 lbs
Reservoir Capacity:	265 gallons
Duplex Reservoir:	Add 47 gallons
Sludge Capacity:	75 gallons



© 2019 StingRay Mfg LLC, all rights reserved. This document contains intellectual property protected by law. StingRay Parts Washer® is a trademark of StingRay.



Pump System & Performance:

High Efficiency, Rated for continuous duty (20 Start/hour without overheating), vertical, centrifugal, seal-less, balanced, enclosed impeller.

Note: All performance data taken at nozzle discharge.

	STANDARD:		UPGRADES: (Simplex)		UPGRADES: (Duplex)	
	20 hp		30 hp	40 hp	55 hp	70 hp
Total System Flow:	269 gpm		301 gpm	319 gpm	356 gpm	371 gpm
Flow per Nozzle:	13.5 gpm		15.1 gpm	16.0 gpm	17.8 gpm	18.6 gpm
System Pressure:	107 psi		134 psi	150 psi	187 psi	203 psi
Blast Velocity:	126 ft/sec		141 ft/sec	149 ft/sec	166 ft/sec	173 ft/sec



Results and Dimensions may vary based on machine configuration.



STINGRAY MANUFACTURING
 2450 Adie Road • St. Louis, MO 63043 USA
 Phone: (314)447-9000 • Fax: (314)447-0909
 Email: sales@stingwash.com • www.stingwash.com