

STINGRAY 5275 SPECIFICATIONS

Standard Features & General Construction:

Oscillating Manifold: Non-Synchronous to the Turntable - Maximizes Cleaning.
Swing Door Retracting, Door-Mounted Turntable: Allows for Maximum Access.
Closed-Loop, Zero Discharge Cleaning Process: Environmentally Friendly.
Heated Fresh Water Rinse: Removes Residual Detergent (Optional).
Automatic Steam Exhaust: Facilitates Flash Drying of Parts.
Non-Intersecting Stainless Steel V-Jet Nozzles: Blasts Parts Clean.
Heavy 7-Gauge, 3/16" Sheet Steel Cabinet.
Electronic Water Level Control: Maintains Proper Solution Level.
Programmable 24-Hour 7-Day Clock: Delivers Simple Operation.
Wash Cycle Timer with Auto Reset: Effortless Cleaning Cycle Programming.
Easy Access Solution Tank: Delivers Trouble-Free Maintenance.
Electronic Door Safety Interlock: Prevents Operation if Switch Fails.
StingRay Blue, 2-Part, 3 mil Epoxy Coating: Withstands Cleaning Chemicals.
Adjustable Electronic Temp Control, Temp Gauge, Digital 2-Line Display
Control Transformer External of Panel: Minimizes Heat.
Low Water Shut-Off: Protects Pumps & Heating System.
Quality Conforms to ISO9001 and OSHA-Compliant



Power Blast Manifold:

OSCILLATING NON- SYNCHRONOUS

Angle of Oscillation:	39 degrees
Frequency of Oscillation:	4 per minute
Number of Wash Nozzles:	24
Type of Nozzle:	Vee-Jet
Nozzle Material:	316 Stainless
Nozzle Spray Pattern:	25 degrees

Heat System:

Operating Temperature:	140 - 190 degrees F
Initial Heat-Up Time:	60 - 90 minutes
Element Size:	60 kW
Gas/Propane Eclipse 80% Eff:	400,000 BTU/hr

Base Machine Work Area Dimensions:

Turntable Diameter:	52 inches
Cleaning Work Height:	75 inches
Turntable Height above Floor:	34.5 inches
Table Load Capacity:	4,000 lbs
Heavy Duty Capacity:	7,000 lbs

Base Machine Overall Dimensions:

Width: (Std Unit)	98 inches
Depth: (Std Unit)	87 inches
Height:	120 inches
Empty Weight:	6100 lbs
Reservoir Capacity:	265 gallons
Duplex Reservoir:	Add 47 gallons
Sludge Capacity:	75 gallons



© 2019 StingRay Mfg LLC, all rights reserved. This document contains intellectual property protected by law. StingRay Parts Washer® is a trademark of StingRay.



Pump System & Performance:

High Efficiency, Rated for continuous duty (20 Start/hour without overheating), vertical, centrifugal, seal-less, balanced, enclosed impeller.

Note: All performance data taken at nozzle discharge.

	STANDARD:		UPGRADES: (Duplex)	
	30 hp		55 hp	70 hp
Total System Flow:	343 gpm		399 gpm	431 gpm
Flow per Nozzle:	14.3 gpm		16.6 gpm	18.0 gpm
System Pressure:	121 psi		163 psi	190 psi
Blast Velocity:	133 ft/sec		155 ft/sec	168 ft/sec



Results and Dimensions may vary based on machine configuration.



STINGRAY MANUFACTURING
 2450 Adie Road • St. Louis, MO 63043 USA
 Phone: (314)447-9000 • Fax: (314)447-0909
 Email: sales@stingwash.com • www.stingwash.com