

# STINGRAY 6048

## METRIC SPECIFICATIONS

### Standard Features & General Construction:

- Oscillating Manifold:** Non-Synchronous to the Turntable - Maximizes Cleaning.
- Swing Door Retracting, Door-Mounted Turntable:** Allows for Maximum Access.
- Closed-Loop, Zero Discharge Cleaning Process:** Environmentally Friendly.
- Heated Fresh Water Rinse:** Removes Residual Detergent (Optional).
- Automatic Steam Exhaust:** Facilitates Flash Drying of Parts.
- Non-Intersecting Stainless Steel V-Jet Nozzles:** Blasts Parts Clean.
- Heavy 4.7 mm Gauge Sheet Steel Cabinet.**
- Electronic Water Level Control:** Maintains Proper Solution Level.
- Programmable 24-Hour 7-Day Clock:** Delivers Simple Operation.
- Wash Cycle Timer with Auto Reset:** Effortless Cleaning Cycle Programming.
- Easy Access Solution Tank:** Delivers Trouble-Free Maintenance.
- Electronic Door Safety Interlock:** Prevents Operation if Switch Fails.
- StingRay Blue, 2-Part, 3 mil Epoxy Coating:** Withstands Cleaning Chemicals.
- Adjustable Electronic Temp Control, Temp Gauge, Digital 2-Line Display**
- Control Transformer External of Panel:** Minimizes Heat.
- Low Water Shut-Off:** Protects Pumps & Heating System.
- Quality Conforms to ISO9001 and OSHA-Compliant**

### Power Blast Manifold:

#### OSCILLATING NON- SYNCHRONOUS

Angle of Oscillation:	39 degrees
Frequency of Oscillation:	4 per minute
Number of Wash Nozzles:	20
Type of Nozzle:	Flat Tapered V-Jet
Nozzle Material:	316 Stainless
Nozzle Spray Pattern:	25 degrees

### Heat System:

Operating Temperature:	60 - 88 degrees C
Initial Heat-Up Time:	70 - 120 minutes
Electric Heat Element Size STD:	60 kW
High-Output Electric Heat:	80 kW
Gas/Propane Eclipse 80% Eff:	117 kW

### Base Machine Work Area Dimensions:

Turntable Diameter:	1520 mm
Cleaning Work Height:	1210 mm
Turntable Height above Floor:	876 mm
Table Load Capacity:	1360 kg
Heavy Duty Capacity:	3170 kg

### Base Machine Overall Dimensions:

Width: (Std Unit)	2690 mm
Depth: (Std Unit)	2310 mm
Height:	2360 mm
Empty Weight:	3020 kg
Reservoir Capacity:	1330 liters
Duplex Reservoir:	Add 178 liters
Sludge Capacity:	303 liters

### Pump System & Performance:

High Efficiency, Rated for continuous duty (20 Start/hour without overheating), vertical, centrifugal, seal-less, balanced, enclosed impeller.

**Note: All performance data taken at nozzle discharge.**

	STANDARD:		UPGRADES: (Simplex)		UPGRADES: (Duplex)	
	15 kW		22 kW	30 kW	41 kW	52 kW
Total System Flow:	1020 lpm		1140 lpm	1200 lpm	1350 lpm	1400 lpm
Flow per Nozzle:	51 lpm		57 lpm	61 lpm	67 lpm	70 lpm
System Pressure:	7.4 bar		9.2 bar	10.5 bar	12.9 bar	14.0 bar
Blast Velocity:	38 mps		43 mps	45 mps	51 mps	53 mps

Results and Dimensions may vary based on machine configuration.



© 2019 StingRay Mfg LLC, all rights reserved. This document contains intellectual property protected by law. StingRay Parts Washer® is a trademark of StingRay.



STINGRAY MANUFACTURING  
 2450 Adie Road • St. Louis, MO 63043 USA  
 Phone: (314)447-9000 • Fax: (314)447-0909  
 Email: sales@stingwash.com • www.stingwash.com