

# STINGRAY 7266 SPECIFICATIONS

## Standard Features & General Construction



- Oscillating Manifold:** Non-Synchronous to the Turntable - Maximizes Cleaning.
- Swing Door Retracting, Door-Mounted Turntable:** Allows for Maximum Access.
- Closed-Loop, Zero Discharge Cleaning Process:** Environmentally Friendly.
- Heated Fresh Water Rinse:** Removes Residual Detergent (Optional).
- Automatic Steam Exhaust:** Facilitates Flash Drying of Parts.
- Non-Intersecting Stainless Steel V-Jet Nozzles:** Blasts Parts Clean.
- Heavy 7-Gauge, 3/16" Sheet Steel Cabinet.**
- Electronic Water Level Control:** Maintains Proper Solution Level.
- Programmable 24-Hour 7-Day Clock:** Delivers Simple Operation.
- Wash Cycle Timer with Auto Reset:** Effortless Cleaning Cycle Programming.
- Easy Access Solution Tank:** Delivers Trouble-Free Maintenance.
- Electronic Door Safety Interlock:** Prevents Operation if Switch Fails.
- StingRay Blue, 2-Part, 3 mil Epoxy Coating:** Withstands Cleaning Chemicals.
- Adjustable Electronic Temp Control, Temp Gauge, Digital 2-Line Display**
- Control Transformer External of Panel:** Minimizes Heat.
- Low Water Shut-Off:** Protects Pumps & Heating System.
- Quality Conforms to ISO9001 and OSHA-Compliant**

### Power Blast Manifold:

#### OSCILLATING NON- SYNCHRONOUS

Angle of Oscillation:	39 degrees
Frequency of Oscillation:	4 per minute
Number of Wash Nozzles:	24
Type of Nozzle:	Vee-Jet
Nozzle Material:	316 Stainless
Nozzle Spray Pattern:	25 degrees

### Heat System:

Operating Temperature:	140 - 190 degrees F
Initial Heat-Up Time:	60 - 120 minutes
Element Size:	80 kW
Gas/Propane Eclipse 80% Eff:	500,000 BTU/hr

### Base Machine Work Area Dimensions:

Turntable Diameter:	72 inches
Cleaning Work Height:	66 inches
Turntable Height above Floor:	38 inches
Table Load Capacity:	3,000 lbs
Heavy Duty Capacity:	7,000 lbs

### Base Machine Overall Dimensions:

Width: (Std Unit)	123 inches
Depth: (Std Unit)	102 inches
Height:	112 inches
Empty Weight:	8,200 lbs
Reservoir Capacity:	550 gallons
Duplex Reservoir:	Add 47 gallons
Sludge Capacity:	80 gallons



### Pump System & Performance:

High Efficiency, Rated for continuous duty (20 Start/hour without overheating), vertical, centrifugal, seal-less, balanced, enclosed impeller.

**Note: All performance data taken at nozzle discharge.**

#### STANDARD:

	<b>30 hp</b>
Total System Flow:	343 gpm
Flow per Nozzle:	14.3 gpm
System Pressure:	121 psi
Blast Velocity:	133 ft/sec

#### UPGRADES: (Duplex)

	<b>55 hp</b>	<b>70 hp</b>
Total System Flow:	399 gpm	431 gpm
Flow per Nozzle:	16.6 gpm	18.0 gpm
System Pressure:	163 psi	190 psi
Blast Velocity:	155 ft/sec	168 ft/sec



© 2019 StingRay Mfg LLC, all rights reserved. This document contains intellectual property protected by law. StingRay Parts Washer® is a trademark of StingRay.



Results and Dimensions may vary based on machine configuration.



STINGRAY MANUFACTURING  
2450 Adie Road • St. Louis, MO 63043 USA  
Phone: (314)447-9000 • Fax: (314)447-0909  
Email: sales@stingwash.com • www.stingwash.com